



imagePRESS V900/V800/V700 COLOUR PRODUCTION DIGITAL PRESS



imagePRESS V900 shown with optional accessories.

Product Specifications

Marking Engine

Technology Electrophotography

Print Resolution 2400 x 2400 dpi

Print Speed	V900	V800	V700
8.5" x 11":	Up to 90 ipm	Up to 81 ipm	Up to 71 ipm
11" x 17":	Up to 45 ipm	Up to 40 ipm	Up to 35 ipm
12" x 18":	Up to 42 ipm	Up to 40 ipm	Up to 35 ipm
13" x 19":	Up to 40 ipm	Up to 38 ipm	Up to 33 ipm
13" x 30":	Up to 23 ipm	Up to 22 ipm	Up to 19 ipm

Paper Size

Standard:	3.94" x 5.83" to 13" x 19.2"
Optional:	5.5" x 5.83" to 13" x 51.2"

Paper Capacity¹

Standard:	Up to 1,650 Sheets
Maximum:	Up to 10,400 Sheets

Paper Weight

Standard:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
Optional:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
Envelopes:²	No. 10 (COM10), ISO-C5, DL, Monarch, 6" x 9", 9" x 12", 10" x 13"

Long Sheets³

Duplex:	Up to 13" x 30"
Simplex:	Up to 13" x 51.2"

Automatic Duplexing³

Paper Size:	Up to 13" x 30"
Paper Weight:	Up to 130 lb. Cover (350 gsm) ⁴

Power Source Single-Phase 208 V, 50/60 Hz, 20 A

Weight

With Canon UI:	573 lb.
With PRISMAsync UI:	592 lb.

Dimensions

With Canon UI:	34.7" W x 34.3" D x 40.9" H
With PRISMAsync UI:	59" W x 34.3" D x 54.5" H

Input Accessories

Multi-Drawer Paper Deck-E1

Paper Capacity:¹	Up to 5,000 Sheets
Paper Size:	5.5" x 7.2" to 13" x 19.2"
Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
Power Source:	110 – 127 V, 60 Hz, 6.4 A
Weight:	392 lb.
Dimensions:	38" W x 31.5" D x 42.5" H

POD Deck Lite-C1

Paper Capacity:¹	Up to 3,500 Sheets
Paper Size:	5.5" x 7.2" to 13" x 19.2"
Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
Power Source:	120 – 127 V, 60 Hz, 2.2 A
Weight:	168 lb.
Dimensions:	24.9" W x 27.0" D x 22.6" H

Input Accessories (Continued):

POD Deck Lite XL-A2	Paper Capacity¹	Up to 13" x 19.2": Up to 3,500 Sheets Up to 13" x 30": Up to 1,000 Sheets
	Paper Size:	5.5" x 7.2" to 13" x 30"
	Paper Weight:	
	Up to 13" x 19.2":	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Up to 13" x 30":	17 lb. Bond to 110 lb. Cover (64 gsm to 300 gsm)
	Power Source:	Single-Phase 208 V AC, 60 Hz, 20 A
	Weight:	249 lb.
Dimensions:	40.2" W x 27" D x 22.6" H	

Stack Bypass-D1	Paper Capacity:¹	Up to 250 Sheets
	Paper Size:	3.94" x 5.83" to 13" x 19.2"
	Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Weight:	3 lb.
	Dimensions:	18" W x 15.1" D x 2.9" H

Long Sheet Feeding and Catch Tray-B1	Paper Capacity:	Up to 1 Sheet
	Paper Size:	4" x 5.83" to 13" x 51.2"
	Paper Weight:	17 lb. Bond to 130 lb. Cover (64 gsm to 350 gsm) ⁵
	Weight:	2 lb.
	Dimensions:	85.6" W x 56.1" D x 56.1" H

Colour Image Reader-P1	Image Sensor:	CCD
	Scan Speed:	Up to 270 ipm (Letter, 300 dpi)
	Document Size:	2.8" x 5.5" to 12" x 24.8"
	Resolution:	Up to 600 x 600 dpi, 256 Gradations
	Tray Capacity:¹	Up to 250 Sheets
	Weight:	51 lb.
	Dimensions:	25.7" W x 23.3" D x 8.6" H

Finishing Accessories

Copy Tray-R2	Paper Capacity:¹	Up to 250 Sheets
	Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Paper Size:	4" x 5.83" to 13" x 19.2"
	Weight:	2.6 lb.
	Dimensions:	16.6" W x 15" D x 6.8" H

Sensing Unit-B1⁵	Tasks:	Front-to-Back Alignment, Colour Accuracy Check, Cross Shade Adjustment, Secondary Transfer Adjustment
	DFE:	PRISMAsync print server V8.3 or Later; imagePRESS Server N500/P400 or Later
	Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Paper Size:	5.5" x 5.83" to 13" x 30"
	Power Supply:	100 – 240 V, 50/60 Hz, 2.5 A
	Dimensions:	20.3" W x 29.5" D x 48.3" H

Document Insertion Unit-R1⁵	Tray Capacity¹	Upper Tray: Up to 200 Sheets Lower Tray: Up to 200 Sheets
	Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Paper Size:	7.2" x 7.2" to 13" x 19.2"
	Power Supply:	100 – 240 V, 50/60 Hz, 1.0 A
	Weight:	134 lb.
	Dimensions:	29.4" W x 31.2" D x 55.4" H

Multi Function Professional Puncher-C1⁵	Paper Weight	
	Punching:	20 lb. Bond to 110 lb. Cover (75 gsm to 300 gsm)
	Creasing:	110 lb. Text to 110 lb. Cover (162 gsm to 300 gsm)
	Paper Size	
	Punching (Single):	Letter-R, Letter, Legal, 11" x 17", 12" x 18"
	Punching (Double):	Letter-R, Legal, 11" x 17", 12" x 18"
	Creasing:	Letter-R, 11" x 17", 12" x 18", 13" x 19"
	Die Set Patterns:	Loose Leaf 3-Hole/5-Hole, Velo Bind 11-Hole, Plastic Comb 19-Hole, Twin Loop 21-Hole/32-Hole, Colour Coil 44-Hole, Crease
	Power Supply:	115 V, 60 Hz, 3.8 A
	Weight:	225 lb.
Dimensions:	17.5" W x 31.3" D x 40.9" H	

GBC eWire Pro⁶	Bound Book Size:¹	15 to 100 Sheets
	Paper Size:	Letter, 5.5" x 8.5", Tab Stock
	Paper Weight:	20 lb. Bond to 110 lb. Cover (75 gsm to 300 gsm)
	Wire Choices:	1/4", 5/16", 3/8", 7/16", 1/2", 9/16"
	Stack Capacity:	Up to 35 Books
	Infeed:	Multi Function Professional Puncher-B1
	Power Supply:	115 V, 60 Hz, 2.8A
	Weight:	500 lb.
	Dimensions:	35.8" x 31.3" x 42.6"

Perfect Binder-F1^{5,6}	Finished Book Size:	5.4" x 7.99" to 8.5" x 11.69"
	Book Thickness:¹	10 to 200 Sheets (Up to 0.98")
	Body Paper Weight:	14 lb. Bond to 43 lb. Bond (52 gsm to 163 gsm)
	Cover Paper Weight:	24 lb. Bond to 110 lb. Cover (90 gsm to 300 gsm)
	Trimming Method:	3-Side Cut/1-Side Cut/No Cut
	Trim Range	
	Top/Bottom:	0.26" to 1.56"
	Side:	0.26" to 1.95"
Power Source:	208 V, 60 Hz, 2.6 A	
Weight:	679 lb.	
Dimensions:	36.3" W x 31.1" D x 51.3" H	

Finishing Accessories (Continued):

High Capacity Stacker-J1⁶	Stack Capacity:¹	Up to 6,000 Sheets
	Top Tray Capacity:¹	Up to 200 Sheets
	Paper Size:	5.5" x 7.2" to 13" x 19.2"
	Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Power Source:	100-240 V AC, 50/60 Hz, 2.5 A
	Weight:	265 lb.
Dimensions:		35.4" W x 29.3" D x 44.9" H

Plockmatic Multi Purpose Stacker^{6,7}	Stack Height	
	Sheets < 25.6":	Up to 11.8"
	Sheets > 25.6":	Up to 5.3"
	Paper Size:	8.3" x 11" to 13" x 30"
	Paper Weight:	100 lb. Text to 130 lb. Cover (148 gsm to 350 gsm)
	Power Source:	100 – 240 V, 50/60 Hz, 2 A
Weight:		168 lb.
Dimensions:		41.8" W x 35.4" D x 26.8" H

Paper Folding Unit-K1⁸	Double Parallel Fold:	Legal, Letter-R
	C/Accordion Fold:	Letter-R
	Z-Fold:	Letter-R, 11" x 17"
	Paper Weight:	14 lb. Bond to 28 lb. Bond (52 gsm to 105 gsm)
	Power Source:	From Finisher
	Weight:	157 lb.
Dimensions:		13.2" W x 31.2" D x 46.9" H

Staple Finisher-AC1/Booklet Finisher-AC2⁹	Tray Capacity¹	
	Top Tray:	Up to 250 Sheets
	Middle Tray:	Up to 250 Sheets
	Lower Tray:	Up to 3,000 Sheets
	Saddle-Stitch Tray:	Up to 30 Booklets
	Paper Weight	
	Stacking:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Corner Stapling:	14 lb. Bond to 140 lb. Index (52 gsm to 256 gsm)
	Booklet-Making:	14 lb. Bond to 140 lb. Index (52 gsm to 256 gsm)
	Staple Positions:	Corner, Double-Side, Eco
	Paper Size	
	Stapling:	Executive, Letter-R, Letter, Legal, 11" x 17"
	Saddle Finisher:	7.7" x 10.6" to 12" x 18"
	Stapling Capacity¹	
	Corner/Double-Side:	Up to 65 Sheets
Eco-Stitch:	Up to 6 Sheets	
Saddle-Stitch:	Up to 20 Sheets	
V-Fold:	Up to 3 Sheets without Stitch	
Power Source:	From the Main Unit	
Weight		
Staple Finisher:	79 lb.	
Booklet Finisher:	132 lb.	
Dimensions:		20.8" W x 24.5" D x 43.3" H

2/3 Hole Puncher Unit-A1¹⁰	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Paper Sizes:	Letter-R
	2-Hole:	Legal, Letter-R, Custom Size (7.2" x 7.2" to 11.8" x 17")
	3-Hole:	11" x 17", Letter, Executive-R, Custom Size (9.5" x 7.2" to 11.8" x 17")
Power Supply:		From Finisher

Staple Finisher-AG1/Booklet Finisher-AG1	Tray Capacity¹	
	Top Tray:	Up to 1,000 Sheets
	Lower Tray:	Up to 4,000 Sheets
	Saddle-Stitch Tray:	Continuous by Belt
	Paper Weight	
	Stacking:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Corner Stapling:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Booklet-Making:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Staple Positions:	Corner, Double-Side, Saddle-Stitch
	Paper Size	
	Stapling:	8.3" x 11" to 11.7" x 17"
	Saddle Finisher:	8.27" x 11" to 13" x 19.2"
	Stapling Capacity¹	
	Corner/Double-Side:	Up to 100 Sheets
	Saddle-Stitch:	Up to 25 Sheets
V-Fold:	Up to 5 Sheets without Stitch	
Power Source:	120-240 V, 60 Hz, 8 A	
Weight		
Staple Finisher:	287 lb.	
Booklet Finisher:	397 lb.	
Dimensions:		31.5" W x 31.2" D x 48.8" H

Long Sheet Catch Tray-C1¹¹	Stack Capacity:¹	100 Sheet
	Paper Size:	4" x 5.83" to 13" x 30"

Long Sheet Catch Tray XL-B1¹²	Stack Capacity¹	
	Up to 30":	Up to 300 Sheets
	Up to 51.2":	Up to 10 Sheets
Paper Size:		3.93" x 5.83" to 13" x 51.2"

Puncher Unit-BS1¹²	Paper Sizes	
	2-Hole:	Legal, Letter-R, Custom Size (7.2" x 7.2" to 11.8" x 17")
	3-Hole:	11" x 17", Letter, Executive-R, Custom Size (9.5" x 7.2" to 11.8" x 17")
	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Punch Waste Capacity:	Up to 6,000 Sheets
Power Supply:		From the Finisher

Finishing Accessories (Continued):

Supported Finishing:	Plockmatic BLM50/35 Professional Booklet Maker, Plockmatic Multi Purpose Stacker
Requirements:	Staple/Booklet Finisher-AGI
Weight:	66 lb.
Dimensions:	35.4" W x 29.3" D x 46.9" H

Booklet Trimmer-G1²	Margin Trimming:	Front-edge Trim
	Trim Amount:	0.08" to 1.1"
	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Power Supply:	From the Finisher
	Weight:	392 lb.
	Dimensions:	82.5" W x 31.1" D x 41" H

Two-Knife Trimmer and Conveyor Set¹³	Margin Trimming:	Top and Bottom
	Trim Amount:	0.08" to 0.59"
	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Power Supply:	120-127 V AC, 50/60 Hz, 4 A
	Weight:	320 lb.
	Dimensions:	21.1" W x 30.3" D x 41" H

SDD Square-Fold Booklet-Maker¹³	Booklet Capacity:¹	Up to 25 Sheets
	Booklet Input Size:	4.71" x 8.27" to 9.6" x 12.6"
	Booklet Output Size:	4.71" x 7.87" to 9.6" x 12.6"
	Paper Weight:	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
	Power Supply:	120 V, 60 Hz, 15 A
	Weight:	154 lb.
	Dimensions:	44.9" W x 23.6" D x 44.9" H

SDD Square-Fold Booklet-Maker with Two-Knife Trim¹³	Booklet Capacity:¹	Up to 25 Sheets
	Booklet Input Size:	4.88" x 5.51" to 9.6" x 12.6"
	Booklet Output Size:	4.88" x 5.51" to 9.6" x 12.6"
	Paper Weight:	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
	Trim Amount:	0.08" to 1.38"
	Power Supply:	120 V, 60 Hz, 15 A
	Weight:	573 lb.
	Dimensions:	62.7" W x 27.6" D x 51.2" H

Plockmatic BLM50/35 Professional Booklet-Maker^{6,14}	Booklet Size:¹	Up to 35/50 Sheets	
	Paper Size:	8.1" x 10.8" to 12.6" x 18.1"	
	Paper Weight	Uncoated:	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
		Coated:	28 lb. Bond to 110 lb. Cover (105 gsm to 300 gsm)
	Trim Amount¹⁵	Face:	0.04" to 0.63"
		Top/Bottom:	0.196" to 1.18"
	Paper Rotating:¹⁶	8.1" x 10.9" to 9.1" x 12.7"	
	Weight:	1,229 lb.	
	Dimensions:	131.1" W x 33.8" D x 42.5" H	

Print Servers

imagePRESS Printer Kit-J1	PDL:	UFR II, PS, PCL 5e/6
	Memory:	4 GB
	Hard Drive:	1 TB

PRISMAsync Print Server⁷	System Software:	Version 9
	CPU:	Intel® Core i5 8500
	Memory:	8 GB
	Hard Drive:	1.5 TB
	OS:	Windows® 10, LTSC
	Standard:	Scheduler, DocBox, G7 Calibration, Page Programmer, Remote Manager, PRISMAlytics Dashboard, Automated Workflows, Multiple Queues, Remote Control
	Optional:	E-Shredding

PRISMAsync Print Server LP⁹	System Software:	Version 9
	CPU:	Intel® Core i5 8500
	Memory:	8 GB
	Hard Drive:	1.5 TB
	OS:	Windows® 10, LTSC
	Standard:	Multiple Queues, Scheduler, Remote Manager, Colour Presets, Pixel Precise Preview, Spot Colour Editing, Calibration, Realistic Preview, Digital Moire
	Optional:	Advanced Colour Management, Power-Up Package, E-Shredding

Print Servers (Continued):

imagePRESS Server N500	Fiery System:	FS500 Pro
	CPU:	Intel Core i5-8500 3.2 GHz up to 4.6 GHz W/ Turbo
	Memory:	8 GB
	Hard Drive:	1.2 TB
	OS:	Windows 10
	Standard:	Fiery Hot Folders, Virtual Printers, Unity Display, Fiery JDF, Fiery Command Workstation 6, Paper Catalog, Fiery Spot-On, Fiery Remote Scan, Media Librarian
Optional:	Impose/Compose, Graphic Arts Pro Package, Job Master, JobFlow	

imagePRESS Server P400	Fiery System:	FS500
	CPU:	Intel Pentium G5400, 3.7 GHz
	Memory:	8 GB
	Hard Drive:	500 GB
	OS:	Linux
	Standard:	Fiery Command WorkStation 6, Paper Catalog, Fiery Spot On, Fiery Remote Scan, Hot Folders License
Optional:	Impose/Compose, Automation Package, ColorRight Package, Job Master, JobFlow	

¹ Based on 20 lb. Bond.

² Envelope Attachment Kit required.

³ POD Deck Lite-XL or Long Sheet Feed Tray-B1 required.

⁴ Stocks longer than 19.2" support up to 110 lb. Cover (300 gsm).

⁵ Staple/Booklet Finisher-AG1 or High Capacity Stacker-J1 required.

⁶ Not available for the imagePRESS V700.

⁷ High Capacity Stacker-J1 required.

⁸ Staple/Booklet Finisher-AG1 required.

⁹ Not available for the imagePRESS V900.

¹⁰ Staple Finisher-AC1 or Booklet Finisher-AC2 required.

¹¹ Copy Tray-R2, Staple/Booklet Finisher-AG1 required.

¹² Staple/Booklet Finisher-AG1 required.

¹³ Booklet Trimmer-G1 required.

¹⁴ High Capacity Stacker-J1 or DFD Adapter and Finisher Bridge-A2 required.

¹⁵ Optional trimmer required.

¹⁶ Optional rotator required.

Canon

www.canon.ca



As an ENERGY STAR® Partner, Canon U.S.A., Inc. qualified these models as meeting the ENERGY STAR® energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered Canadian marks. Canon and imagePRESS are registered trademarks of Canon Inc. in Canada and may also be registered trademarks or trademarks in other countries.

PRISMA is a registered trademark of Canon Production Printing Netherlands B.V. All other referenced product names and marks are trademarks of their respective owners. Some printer output images may be simulated. Specifications and availability subject to change without notice. Not responsible for typographical errors.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada Inc. intend to cooperate with Law Enforcement Agencies in connection with claims on unauthorized copying.

©2022 Canon Canada Inc. All rights reserved.

